RUE725 Electric UTV



TECHNICAL SPECIFICATIONS

RUE725

Seats	2 Seaters
Configuration	EEC Standard
Drive system	RWD
Motor	motor 7.5KW
Electricity consumption per charge	10Kwh
Packing dimensions (L × W × H)	2330*1830*1270 mm
Container loading quantity	6 units /20'GP ; 14 unit/ 40'HQ
Gross weight	840 kgs
Front suspension	Dual A-Arm 185.42mm(7.3") Travel
Rear suspension	Dual A-Arm 85.42mm(7.3") Travel
Front/rear brakes	4-Wheel Hydraulic Disc
Parking brake	Hand-Actuated
Wheelbase	1905mm
Minimum ground clearance	220 mm
Minimum turning radius	3.5 m
Max. speed	60 km/h
Climbing ability	<=30°
Hitch towing rating	500 kgs
Carrying capacity	340 kgs
Net weight	788 KGS
Cargo bed dimensions (L × W × H)	(L x W x H)1180×930×340mm
Cargo bed capacity	185 KGS
Overall vehicle dimensions (L × W × H)	(L x W x H)2950x1430x1780mm
Battery	72V, 150Ah Lead acid colloidal battery
Range per charge	80-100km of 1 full time charge
Charging time	6-8 hours
Road tires	Front Tires: 175/65 R14 82H / Rear Tires: 175/65 R14 82H
Colors	Black , Green, Blue , Yellow, Red , White,
Included equipment	Top roof; rear mirror; front bumper; tires; electric lifter
Additional listed feature	Electric power steering
Optional parts	Winch; receiver and ball; soft top + door; front bumper spot light; upper spot light; vehicle cover; kick guards; rear bumper; plow; off-road tires
Optional colors	Matte colors and two colors
Optional lithium battery	BAK-73.6V-150A; BAK-76.8V-230A. For 2-SEATER and 4-SEATER UTV

RUE725X Electric UTV



TECHNICAL SPECIFICATIONS

RUE725X

Seats	2 Seaters
Configuration	EEC Standard
Drive system	4WD/2WD switch
Motor	motor 7.5KW+3KW
Electricity consumption per charge	10Kwh
Packing dimensions (L × W × H)	2330*1830*1270 mm
Container loading quantity	6 units /20'GP ; 14 unit/ 40'HQ
Gross weight	840 kgs
Front suspension	Dual A-Arm 185.42mm(7.3") Travel
Rear suspension	Dual A-Arm 85.42mm(7.3") Travel
Front/rear brakes	4-Wheel Hydraulic Disc
Parking brake	Hand-Actuated
Wheelbase	1905mm
Minimum ground clearance	220 mm
Minimum turning radius	3.5 m
Max. speed	60 km/h
Climbing ability	<=30°
Hitch towing rating	500 kgs
Carrying capacity	340 kgs
Net weight	848 KGS
Cargo bed dimensions (L × W × H)	(L x W x H)1180×930×340mm
Cargo bed capacity	185 KGS
Overall vehicle dimensions (L × W × H)	(L x W x H)2950x1430x1780mm
Battery	72V, 150Ah Lead acid colloidal battery
Range per charge	80-100km of 1 full time charge
Charging time	6-8 hours
Road tires	Front Tires: 175/65 R14 82H / Rear Tires: 175/65 R14 82H
Colors	Black , Green, Blue , Yellow, Red , White,
Included equipment	Top roof; rear mirror; front bumper; tires; electric lifter
Additional listed feature	Electric power steering
Optional parts	Winch; receiver and ball; soft top + door; front bumper spot light; upper spot light; vehicle cover; kick guards; rear bumper; plow; off-road tires
Optional colors	Matte colors and two colors
Optional lithium battery	BAK-73.6V-150A; BAK-76.8V-230A. For 2-SEATER and 4-SEATER UTV

RUE725D Electric UTV



TECHNICAL SPECIFICATIONS

RUE725D

Seats	4 Seaters
Configuration	Standard
Drive system	RWD
Motor	motor 7.5KW
Electricity consumption per charge	10Kwh
Packing dimensions (L × W × H)	3100*2260*1150 mm
Container loading quantity	2 units /20'GP ; 6 unit/ 40'HQ
Gross weight	1050 KGS
Front suspension	Dual A-Arm 185.42mm(7.3") Travel
Rear suspension	Dual A-Arm 85.42mm(7.3") Travel
Front/rear brakes	4-Wheel Hydraulic Disc
Parking brake	Hand-Actuated
Wheelbase	2710 mm
Minimum ground clearance	280 mm
Minimum turning radius	6 m
Max. speed	60 km/h
Climbing ability	<=30°
Hitch towing rating	500 kgs
Carrying capacity	340 kgs
Net weight	838 KGS
Cargo bed dimensions (L × W × H)	(L x W x H)1180×930×340mm
Cargo bed capacity	185 KGS
Overall vehicle dimensions (L × W × H)	(L x W x H) 3695*1495*1890mm
Battery	72V, 150Ah Lead acid colloidal battery
Range per charge	80-100km of 1 full time charge
Charging time	6-8 hours
Road tires	Front Tires: 175/65 R14 82H / Rear Tires: 175/65 R14 82H
Colors	Black , Green, Blue , Yellow, Red , White,
Included equipment	Top roof; rear mirror; front bumper; tires; electric lifter
Additional listed feature	Electric power steering
Optional parts	Winch; receiver and ball; soft top + door; front bumper spot light; upper spot light; vehicle cover; kick guards; rear bumper; plow; off-road tires
Optional colors	Matte colors and two colors
Optional lithium battery	BAK-73.6V-150A; BAK-76.8V-230A. For 2-SEATER and 4-SEATER UTV

RUE725DX Electric UTV



TECHNICAL SPECIFICATIONS

RUE725DX

Seats	4 Seaters
Configuration	Standard
Drive system	4WD/2WD switch
Motor	motor 7.5KW+3KW
Electricity consumption per charge	10Kwh
Packing dimensions (L × W × H)	3100*2260*1150 mm
Container loading quantity	2 units /20'GP ; 6 unit/ 40'HQ
Gross weight	1050 KGS
Front suspension	Dual A-Arm 185.42mm(7.3") Travel
Rear suspension	Dual A-Arm 85.42mm(7.3") Travel
Front/rear brakes	4-Wheel Hydraulic Disc
Parking brake	Hand-Actuated
Wheelbase	2710 mm
Minimum ground clearance	280 mm
Minimum turning radius	6 m
Max. speed	60 km/h
Climbing ability	<=30°
Hitch towing rating	500 kgs
Carrying capacity	340 kgs
Net weight	898 KGS
Cargo bed dimensions (L × W × H)	(L x W x H)1180×930×340mm
Cargo bed capacity	185 KGS
Overall vehicle dimensions (L × W × H)	(L x W x H) 3695*1495*1890mm
Battery	72V, 150Ah Lead acid colloidal battery
Range per charge	80-100km of 1 full time charge
Charging time	6-8 hours
Road tires	Front Tires: 175/65 R14 82H / Rear Tires: 175/65 R14 82H
Colors	Black , Green, Blue , Yellow, Red , White,
Included equipment	Top roof; rear mirror; front bumper; tires; electric lifter
Additional listed feature	Electric power steering
Optional parts	Winch; receiver and ball; soft top + door; front bumper spot light; upper spot light; vehicle cover; kick guards; rear bumper; plow; off-road tires
Optional colors	Matte colors and two colors
Optional lithium battery	BAK-73.6V-150A; BAK-76.8V-230A. For 2-SEATER and 4-SEATER UTV

RUE725DX-B Electric UTV



TECHNICAL SPECIFICATIONS

RUE725DX-B

Seats	2 seaters with large cargo bed
Configuration	Customize
Drive system	4WD/2WD switch
Motor	motor 7.5KW+3KW
Electricity consumption per charge	10Kwh
Packing dimensions (L × W × H)	3100*2260*1150 mm
Container loading quantity	2 units /20'GP ; 6 unit/ 40'HQ
Gross weight	1050 KGS
Front suspension	Dual A-Arm 185.42mm(7.3") Travel
Rear suspension	Dual A-Arm 85.42mm(7.3") Travel
Front/rear brakes	4-Wheel Hydraulic Disc
Parking brake	Hand-Actuated
Wheelbase	2710 mm
Minimum ground clearance	280 mm
Minimum turning radius	6 m
Max. speed	60 km/h
Climbing ability	<=30°
Hitch towing rating	500 kgs
Carrying capacity	340 kgs
Cargo bed dimensions (L × W × H)	1500*1282*285mm
Cargo bed capacity	300 KGS
Overall vehicle dimensions (L × W × H)	3695*1495*1890mm
Battery	72V, 150Ah Lead acid colloidal battery
Range per charge	80-100km of 1 full time charge
Charging time	6-8 hours
Road tires	Front Tires: 175/65 R14 82H / Rear Tires: 175/65 R14 82H
Colors	Black , Green, Blue , Yellow, Red , White,
Included equipment	Top roof; rear mirror; front bumper; tires; electric lifter
Additional listed feature	Electric power steering
Optional parts	Winch; receiver and ball; soft top + door; front bumper spot light; upper spot light; vehicle cover; kick guards; rear bumper; plow; off-road tires
Optional colors	Matte colors and two colors
Optional lithium battery	BAK-73.6V-150A; BAK-76.8V-230A. For 2-SEATER and 4-SEATER UTV

K1 Golf Cart



TECHNICAL SPECIFICATIONS

K1

Model design	Common-mold design
Available versions	Civilian version; off-road version